
山 东 道 恩 钛 业 股 份 有 限 公 司

R-2395 金红石型钛白粉

产品说明书

1. 产品介绍

本产品是经过硅、铝无机表面处理，有机表面处理的金红石型钛白颜料，具有白度高、分散性好、高消色力、高耐候性等特征。

2. 应用领域

本产品适用于室内外涂料、乳胶漆、油墨、造纸、塑料、色母粒等领域。

3. R-2395 金红石型钛白粉的技术指标

二氧化钛含量	≥90.0%
金红石含量	≥97.0%
无机包膜	有
有机包膜	有
平均粒度	0.25 μ m
密度	4.0g/cm ³
颜色 CIEL*	≥97.5
吸油量	≤23
耐候性	高
ISO591 分类	R2
ASTMD476	V

包装： 25kg 纸复合袋

1000kg 吨托

Advance Industrial Solution

Tel : +92-300-1617005 , +92-340-2459543 , +92-328-0296377

Address : 394b1, Johar Town Rd, Block R Phase 2 Johar Town, Lahore

E-mail : info@advanceindustrialsolutions.com Web : www.advanceindustrialsolutions.com

R-2395 Rutile Titanium Dioxide

Technical Data Sheet

1. Product introduction

The product is Rutile titanium dioxide pigment with silicon, aluminum inorganic surface treatment, organic surface treatment, with high whiteness, good dispersibility, good tinting strength, high weathering resistance etc.

2. Application field

The product is suitable for indoor and outdoor coating, latex paint, ink, paper, plastic, masterbatches, etc.

3. R-2395 Rutile Titanium Dioxide technical specifications

TiO₂ content	More than 90.0%
Rutile transformation rate	More than 97.0%
Inorganic coating	Silicon, aluminum
Organic treatment	Yes
Particle size	0.25μm
Density	4.0g/cm³
Color	More than 97.5
Oil absorption	≤23
Weather resistance	High
Standard classification(ISO 591)	Rutile
ASTMD476	V

Packing: 25kg Plastic and paper

1000kg Ton bags